

# ARABESQUE



— EST 1967 —

## FACINGS

OF AMERICA

# Arabesque


4-1/2" Flat

11 pcs. = 1 sq.ft. / 165 pcs. = 15 sq.ft. per box

Flat



ARB-1  
Hampton (Matte)



ARB-2  
Laguna



ARB-3  
Coronado (Glossy)



ARB-5  
Pompeii



ARB-6  
Pismo

**Note** Wide shade variation inherent in this series.  
Recommended grout joint 1/8" or greater.



# Arabesque

4-1/2" Embossed

11 pcs. = 1 sq.ft. / 132 pcs. = 12 sq.ft. per box

Embossed



ARB-1E  
Hampton (Matte)



ARB-2E  
Laguna



ARB-3E  
Coronado (Glossy)



ARB-4E  
Avalon



ARB-5E  
Pompeii




**Note** Wide shade variation inherent in this series.  
Recommended grout joint 1/8" or greater.

## Available Trims


### Jolly Piece



Jolly Piece 9/16" x 6"



Jolly Piece 1/2" x 6"



**Note** Please note the Jolly pieces are coordinating trims that are fired at different times than the field tile. In this regard, there can be wide shade variations between the field and trim pieces.



**Note** Wide shade variation inherent in this series.

# ARABESQUE

4 1/2" FLAT & EMBOSSED



Mix and match six elegant colorways in flat and embossed styles to bring your own unique vision to life!

Coordinating Trim: Jolly Piece 9/16" x 6" Bead | Jolly Piece 1/2" x 6" Surface Bullnose

*Please note the jolly pieces are coordinating trims that are fired at different times than the field tile. In this regard, there can be wide shade variations between the field and trim pieces.*

## RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All countertop applications - residential and commercial (Flat only)
- Fireplace hearth (Flat only)
- Fireplace surround and firebox
- Light commercial flooring applications and all residential flooring applications (Flat only)
- All interior wall applications - residential and commercial
- All exterior wall applications - residential and commercial including building facades, swimming pools, fountains, outdoor kitchens, and regions that experience extreme weather conditions, subject to the method of installation

## INSTALLATION METHOD

- Please refer to the TCNA handbook for installation method: <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting, and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint: Minimum 1/8"
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

## TECHNICAL DATA

- Japanese Porcelain - fired at approx. 2300° Fahrenheit
- Chemical Resistant
- VOC Free
- Frost Proof - *subject to method of installation*
- Water absorbency
  - Bisque less than 1%
  - Glazed surface 0%
- TCNA - MOH's Scale Rating: 7
- TCNA - DCOF Average Ratings:
  - ARB-1, 4, 5, 6: 0.36
  - ARB-2, 3: 0.22

### Flat:

- Loose pieces: 11 pcs. = 1 sq. ft. / 165 pcs. = 15 sq. ft. per box
- Weight: 3.5 lbs. per 11 pcs. / 52 lbs. per box
- Thickness: 5/16"

### Embossed:

- Loose pieces: 11 pcs. = 1 sq. ft. / 132 pcs. = 12 sq. ft. per box
- Weight: 4.5 lbs. per 11 pcs. / 54 lbs. per box
- Thickness: 7/16"

- Pre-consumer recycled content - 52%

Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.

We will endeavor to resolve any issues that may arise with material purchased prior to installation.