



ARGENT NATURAL 24"X48" RT

## COLORS



ARGENT NATURAL 24"X48" RT



IRON NATURAL 24"X48" RT



CARBON NATURAL 24"X48" RT



DUSK NATURAL 24"X48" RT



STONE NATURAL 24"X48" RT

Introducing Echo, an Italian-made porcelain tile featuring a clean concrete aesthetic.  
 Echo is characterized by a soft color palette and subtle, yet realistic movement.  
 Versatility and durability make Echo suitable for both residential and commercial settings.

## ADDITIONAL SIZES

12"X24", 24"X24" PRESSED  
 12"X24", 24"X24" RT  
 12"X24", 24"X24" RT POLISHED  
 12"X24", 24"X24" TEXTURED R11  
 24"X48" RT POLISHED  
 24"X24" RT 2CM R11 (CARBON, IRON, & DUSK ONLY)

## SPECIALTY

2"X2" MOSAIC  
 12"X24" STAIR TREAD WITH SBN  
 8"X24" RT WALL TILE ARGENT/IRON  
 8"X24" RT WALL TILE CARBON/IRON  
 8"X24" RT WALL TILE DUSK  
 8"X24" RT WALL TILE STONE

## APPLICATIONS

INTERIOR WALLS & FLOORS  
 EXTERIOR WALLS & FLOORS  
 STEAM SHOWERS  
 POOLS & SPAS

## ECHO

NUMBER OF FACES: 5

COLOR BODY PORCELAIN

FLOOR TILES	CLASSIFICATION IN ACCORDANCE WITH EN 14411 ANNEXE G B la UGL		
PHYSICAL-CHEMICAL PROPERTIES	STANDARD OF TEST	REQUIREMENTS	AVERAGE RATING
THICKNESS	ISO 10545-02	3/8"   $\pm 5\%$	CONFORMS
WATER ABSORPTION	ISO 10545-03	$\leq .5\%$	CONFORMS
CHEMICAL RESISTANCE	ISO 10545-13	CLASS UB MIN (UGL)	CONFORMS
BREAK RESISTANCE	ISO 10545-04	$S \geq 1300 \text{ N}$	CONFORMS
		$R \geq 35 \text{ N/MM}^2$	
DEEP SCRATCH RESISTANCE	ISO 10545-06	$\leq 175 \text{ MM}^3$	CONFORMS
THERMAL SHOCK RESISTANCE	ISO 10545-09	NO VISIBLE DEFECT	CONFORMS
FROST RESISTANCE	ISO 10545-12	RESISTANT	CONFORMS
STAIN RESISTANCE	ISO 10545-14	CLASS 3 MIN	CONFORMS
SLIP RESISTANCE	DIN 51130	CLASSIFICATION R	R9
DYNAMIC COEFFICIENT OF FRICTION	ANSI A137.1:2012	$\geq .42 \text{ WET}$	0.30

PLEASE VIEW ACTUAL MATERIAL BEFORE MAKING YOUR SELECTION, AS PRINTED IMAGES ARE ONLY REPRESENTATIVE.  
 SHADE VARIATION IS TO BE EXPECTED.

— EST 1967 —  
**FACINGS**  
 —  
 OF AMERICA