



HALO NATURAL


COLORS




WISP NATURAL 24\"/>



SILK NATURAL 24\"/>



HALO NATURAL 24\"/>



GRAIN NATURAL 24\"/>

Inspired by reflectant angles of cut gems, Facet is a modern, porcelain version of traditional terrazzo. The effect of quartz fragments creates lightness, shadow, and striking movement. Facet is a unique surface suitable for both residential and commercial interior and exterior applications.

ADDITIONAL SIZES

12"X24" NATURAL
48"X48" NATURAL (WISP & GRAIN ONLY)

SPECIALTY

13"X24" STAIR TREAD NATURAL
13"X13" STAIR CORNER NATURAL

TRIM

3"X24" SURFACE BULLNOSE

APPLICATIONS

INTERIOR WALLS & FLOORS
EXTERIOR WALLS & FLOORS
STEAM SHOWERS
SUBMERGED APPLICATIONS

FLOOR TILES	CLASSIFICATION IN ACCORDANCE WITH EN 14411 ANNEXE G B la UGL		
FORMAT	RECTIFIED PORCELAIN		
NUMBER OF FACES	30		
ACTUAL DIMENSIONS	11.81"X23.62" (12"X24")	23.62"X23.62" (24"X24")	47.25"X47.25" (48"X48")
THICKNESS	9MM		
PHYSICAL-CHEMICAL PROPERTIES	STANDARD OF TEST	REQUIREMENTS	AVERAGE RATING
WATER ABSORPTION	ISO 10545-03	≤ .5%	CONFORMS
RESISTANCE TO BENDING	ISO 10545-04	> 35N/MM ²	> 52N/MM ²
BREAKING STRENGTH	ISO 10545-04	> 1300 N	> 2500 N
DEEP SCRATCH RESISTANCE	ISO 10545-06	< 145 MM ³	< 109 MM ³
THERMAL SHOCK RESISTANCE	ISO 10545-09	PASS ACCORDING TO EN ISO 10545-1	CONFORMS
CHEMICAL RESISTANCE	ISO 10545-13	CLASS UB MIN (UGL)	GLA/GHA CONFORMS
FROST RESISTANCE	ISO 10545-12	PASS ACCORDING TO EN ISO 10545-1	CONFORMS
STAIN RESISTANCE	ISO 10545-14	CLASS 3 MIN	CLASS 5
SLIP RESISTANCE	DIN 51130	MIN. R9	R9 NATURAL
	DIN 51097	MIN. CLASS A	CLASS A NATURAL
DYNAMIC COEFFICIENT OF FRICTION	ANSI A137.1:2012	≥ .42 WET	CONFORMS

PLEASE VIEW ACTUAL MATERIAL BEFORE MAKING YOUR SELECTION, AS PRINTED IMAGES ARE ONLY REPRESENTATIVE. SHADE VARIATION IS TO BE EXPECTED.