



ELLE 5"X5" & 5-1/2" HEXAGON


COLORS




GRAN 5"X5"



MIO 5"X5"



ELLE 5"X5"



AMAN 5-1/2" HEX



FES 5-1/2" HEX




GRAN 5-1/2" HEX



MIO 5-1/2" HEX



ELLE 5-1/2" HEX



BAYA 5-1/2" HEX

Introducing Zeli, a Spanish-made glazed tile inspired by traditional handmade Moroccan zellige tiles. Zeli's bright palette and distinctive variation bring character to any setting. Versatility and durability make it suitable for a variety of residential and commercial applications.

APPLICATIONS

5-1/2" HEXAGON
 INTERIOR WALLS & FLOORS
 EXTERIOR WALLS & FLOORS

5"X5" FIELD TILE
 INTERIOR WALLS ONLY

ZELI

5"X5" GLAZED WALL TILE
 5-1/2" HEXAGON GLAZED PORCELAIN TILE

FLOOR TILES		CLASSIFICATION IN ACCORDANCE WITH EN 14411-GROUP BIa	
PHYSICAL-CHEMICAL PROPERTIES	STANDARD OF TEST	VALUE	
THICKNESS	UNE-EN 14411	1/4" THICKNESS	MEETS ALL REQUIREMENTS
WATER ABSORPTION	ISO 10545-03	E ≤ .5%	
FLEXION RESISTENCE	ISO 10545-04	≥35 N/mm ²	
ABRASION RESISTANCE	ISO 10545-07	4	
THERMAL SHOCK RESISTANCE	ISO 10545-09	COMPLIES	
CRACKING RESISTANCE	ISO 10545-11	COMPLIES	
FROST RESISTANCE	ISO 10545-12	COMPLIES	
CHEMICAL RESISTANCE	ISO 10545-13	COMPLIES	
STAIN RESISTANCE	ISO 10545-14	5	
SLIP RESISTANCE (Rd)	ENV12633	CLASS 2	
SLIP RESISTANCE ®	DIN 51130	R9	
DYNAMIC COEFFICIENT OF FRICTION	ANSI A137.1	>0.50	

WALL TILES		CLASSIFICATION IN ACCORDANCE WITH EN 14411-GROUP BIII	
PHYSICAL-CHEMICAL PROPERTIES	STANDARD OF TEST	VALUE	
THICKNESS	UNE-EN 14411	1/4" THICKNESS	MEETS ALL REQUIREMENTS
WATER ABSORPTION	ISO 10545-03	E > 10%	
FLEXION RESISTENCE	ISO 10545-04	>15 N/mm ²	
THERMAL SHOCK RESISTANCE	ISO 10545-09	COMPLIES	
LINEAR THERMAL EXPANSION	ISO 10545-08	<7*10 ⁻⁶ °C ⁻¹	
CRAZING RESISTANCE	ISO 10545-11	COMPLIES	
CLEANING PRODUCT RESISTANCE	ISO 10545-13	GA	
STAIN RESISTANCE	ISO 10545-14	5	

PLEASE VIEW ACTUAL MATERIAL BEFORE MAKING YOUR SELECTION, AS PRINTED IMAGES ARE ONLY REPRESENTATIVE. SHADE VARIATION IS TO BE EXPECTED.