

EST 1967

FACINGS

OF AMERICA

^ *Vamos a* ^
LAS PLAYAS

1x1 • 1x2 • Hexagon • Subway




1x1 in Bolsa Chica

LAS PLAYAS

Gorgeous Las Playas (“The Beaches”) blends the incomparable beauty of art glass with the durability and through-body color of genuine cast glass – as only we can do! Each tile features a stunning fusion of molten opaque color swirling onto a white base, evoking the dynamic coastlines from which the colors take their names.

1X1



Coronado

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



San Clemente

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



Solana

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



Bolsa Chica

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)




Catalina

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



Encinitas

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



La Jolla

70% Non-Irid/ 30% Irid
Straight Set Blend
7/8" x 7/8" (22 x 22mm)
Sheet Size: 12 3/8" x 12 3/8"
(314 x 314mm)



1x1 in Bolsa Chica


1X2



Coronado
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



San Clemente
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



Solana
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



Bolsa Chica
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



Catalina
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



Encinitas
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)



La Jolla
70% Non-Irid/ 30% Irid
Offset Blend
7/8"x 1 7/8" (22 x 48mm)
Sheet Size: 11 3/8"x 11 1/2"
(289 x 292mm)


HEXAGON



Coronado
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



San Clemente
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



Solana
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



Bolsa Chica
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



Catalina
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



Encinitas
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)



La Jolla
1 5/8" Hexagon (41mm)
Sheet Size: 11 15/16" x 11 13/16"
(303 x 300mm)

SUBWAY




Coronado
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



San Clemente
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



Solana
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



Bolsa Chica
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



Catalina
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



Encinitas
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



La Jolla
Subway
1 3/8"x 4 1/4" (35 x 108mm)
Sheet Size: 10 1/2"x 11 3/8"
(267 x 289mm)



Subway in Catalina

RECOMMENDED APPLICATIONS

	TILE TYPE	WALLS		SHOWERS		STEAM SHOWERS ²		COUNTERTOPS		SUBMERGED		FLOORS		FLOOR USAGE LEVEL				
	LOCATION	Interior	Exterior	Walls	Floors	Walls	Floors	Powder Room	Kitchen	Pools & Spas	Water Features	Interior	Exterior	Light Residential	Residential	Heavy Residential	Light Commercial	
Art Glass	DEVOTION¹																	
	Mosaic (Mounted)	•	•	•		•												
	Field Tile (Unmounted)	•		•		•												
Cast Glass	ZOETIC																	
	All	•	•	•		•				•	•							
	MUSE, LAS PLAYAS & LAS ISLAS																	
	Iridescent	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Non-Iridescent	•	•	•		•		•		•	•							
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Textura	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Light Residential	Residential flooring areas subject to soft-soled footwear or normal footwear traffic without heavy dirt. Some examples would be: interior rooms such as bathrooms and bedrooms without exterior access.
Residential	Residential flooring areas that are subject to soft-soled footwear or normal footwear traffic with small amounts of abrasive soil. Some examples would be: living or dining rooms.
Heavy Residential	Residential flooring areas that are subject to normal footwear traffic with occasional amounts of abrasive soil. Some examples would be: halls, kitchens and corridors.
Light Commercial	Non-industrial, commercial flooring areas that are subject to normal footwear traffic (less than 50 people per hour) with occasional amounts of abrasive soil. Some examples would be: boutique showrooms and corporate office spaces.

In general, Vendor only recommends opaque tile in steam showers. However, in some instances, translucent tile may be used when installed with specific installation materials.

FIREPLACES: We recommend ALL Glass & Tile products for use on fireplace surrounds (wall tile) and/or hearth (floor tile only) applications. Glass & Tile products are NOT recommended for use inside fireboxes.

SALT WATER POOLS: All Glass & Tile products recommended for use in pools (see chart above) are not adversely affected by exposure to salt water and are recommended for use in both fresh water and salt water pools.

SIZE LIMITATIONS: Tiles with any edge longer than 5" or trim tile with any edge longer than 2.5" are not recommended for use on shower floors or in pool or water feature applications.

TEST RESULTS

Dynamic Coefficient of Friction Statement

Tiles with Dynamic Coefficient of Friction (DCOF) values less than .42 are not recommended for use on level, interior spaces expected to be walked upon when wet. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery, resulting in a fall and personal injury. However, this criteria does not apply to shower floors. The suitability of a tile for use on shower floors will be impacted by the format size of the tile, the size and frequency of the grout joints, a lack of footwear during showering and the expectation that the walking surface is wet. Due to the increase in drainage and reduction in the potential to hydroplane provided by a higher number of grout joints and an increase in traction of a bare foot, tiles that are 2" x 2" or smaller, that test below .42 DCOF, may be suitable for use on shower floors. See ANSI A326.3 American National Standard Test Method For Measuring Dynamic Coefficient of Friction of Hard Surface Flooring Materials, available at www.tcnatile.com, for additional information.

TEST RESULTS									
TEST	ANSI A326.3	C648	A137.2-7.8	ISO 10545-4		C424	C650	C373	C1026
Collections	Dynamic Coefficient of Friction	Breaking Strength*	Compressive Strength**	Breaking Strength	Modulus of Rupture	Crazing Resistance	Chemical Resistance	Water Absorption	Freeze-Thaw Resistance
MUSE, LAS PLAYAS, LAS ISLAS & ZOETIC									
Irid	<.42	≥ 350 lbf	≥ 2500 psi	N/A	N/A	No Effect 1 cycle @ 150 psi	No Effect	<.5%, Impervious	Pass
Non-Irid	<.42								
Matte	>.42								
Textura	>.42								

*For tile measuring greater than or equal to 1" x 1".

**For tile measuring smaller than 1" x 1".

