

^ *Flow Into* ^
ZOETIC

Prelude A, B & C

EST 1967

FACINGS

OF AMERICA

Prelude Pattern C in Pewter

.....

ZOETIC

Zoetic features a dimensional surface that catches and reflects light with striking depth and movement! Assembled to order in three layouts, they bring lasting style to any space, inside or out.

PRELUDE A



PRELUDE B



PRELUDE C






Satin Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)






Silverlight Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)




Sandbar Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)



Bronze Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)



Peacock Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)



Pewter Irid
Sheet Size: 11 1/2" x 11 1/2"
(292 x 292mm)

RECOMMENDED APPLICATIONS

	TILE TYPE	WALLS		SHOWERS		STEAM SHOWERS ²		COUNTERTOPS		SUBMERGED		FLOORS		FLOOR USAGE LEVEL				
	LOCATION	Interior	Exterior	Walls	Floors	Walls	Floors	Powder Room	Kitchen	Pools & Spas	Water Features	Interior	Exterior	Light Residential	Residential	Heavy Residential	Light Commercial	
Art Glass	DEVOTION¹																	
	Mosaic (Mounted)	•	•	•		•												
	Field Tile (Unmounted)	•		•		•												
Cast Glass	ZOETIC																	
	All	•	•	•		•				•	•							
	MUSE, LAS PLAYAS & LAS ISLAS																	
	Iridescent	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	Non-Iridescent	•	•	•		•		•		•	•							
Matte	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Textura	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	

Light Residential	Residential flooring areas subject to soft-soled footwear or normal footwear traffic without heavy dirt. Some examples would be: interior rooms such as bathrooms and bedrooms without exterior access.
Residential	Residential flooring areas that are subject to soft-soled footwear or normal footwear traffic with small amounts of abrasive soil. Some examples would be: living or dining rooms.
Heavy Residential	Residential flooring areas that are subject to normal footwear traffic with occasional amounts of abrasive soil. Some examples would be: halls, kitchens and corridors.
Light Commercial	Non-industrial, commercial flooring areas that are subject to normal footwear traffic (less than 50 people per hour) with occasional amounts of abrasive soil. Some examples would be: boutique showrooms and corporate office spaces.

¹ The following Devotion colors are NOT recommended for exterior applications: Lustre and Gilt.

² In general, Facings of America only recommends opaque tile in steam showers. However, in some instances, translucent tile may be used when installed with specific installation materials.

FIREPLACES: We recommend ALL products for use on fireplace surrounds (wall tile) and/or hearth (floor tile only) applications. Glass & Tile products are NOT recommended for use inside fireboxes.

SALT WATER POOLS: All products recommended for use in pools (see chart above) are not adversely affected by exposure to salt water and are recommended for use in both fresh water and salt water pools.

SIZE LIMITATIONS: Tiles with any edge longer than 5" or trim tile with any edge longer than 2.5" are not recommended for use on shower floors or in pool or water feature applications.

TEST RESULTS

Dynamic Coefficient of Friction Statement

Tiles with Dynamic Coefficient of Friction (DCOF) values less than .42 are not recommended for use on level, interior spaces expected to be walked upon when wet. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery, resulting in a fall and personal injury. However, this criteria does not apply to shower floors. The suitability of a tile for use on shower floors will be impacted by the format size of the tile, the size and frequency of the grout joints, a lack of footwear during showering and the expectation that the walking surface is wet. Due to the increase in drainage and reduction in the potential to hydroplane provided by a higher number of grout joints and an increase in traction of a bare foot, tiles that are 2" x 2" or smaller, that test below .42 DCOF, may be suitable for use on shower floors. See ANSI A326.3 American National Standard Test Method For Measuring Dynamic Coefficient of Friction of Hard Surface Flooring Materials, available at www.tcnatile.com, for additional information.

TEST RESULTS									
TEST	ANSI A326.3	C648	A137.2-7.8	ISO 10545-4		C424	C650	C373	C1026
Collections	Dynamic Coefficient of Friction	Breaking Strength*	Compressive Strength**	Breaking Strength	Modulus of Rupture	Crazing Resistance	Chemical Resistance	Water Absorption	Freeze-Thaw Resistance
MUSE, LAS PLAYAS, LAS ISLAS & ZOETIC									
Irid	<.42	≥ 350 lbf	≥ 2500 psi	N/A	N/A	No Effect 1 cycle @ 150 psi	No Effect	<.5%, Impervious	Pass
Non-Irid	<.42								
Matte	>.42								
Textura	>.42								

*For tile measuring greater than or equal to 1" x 1".

**For tile measuring smaller than 1" x 1".



1x2 in Montego

MINIMUM ORDER QUANTITY

All In-Stock items are sold in full boxes. See the chart below for an overview of our program and please note that you can only order in increments of one box. *Half boxes or individual pieces are not available for purchase.*

Tile Type	Pattern Names & Shapes	MOQ/ Order Increment
Paper-Faced Tile 	Muse & Make It Your Own (Muse)	 1 box = 10 sheets
Film-Faced Artisan Cast Glass 	Las Playas, Las Islas and Zoetic	 1 box = 10 sheets
Film-Faced Luxury Art Glass 	Devotion & Make It Your Own (Devotion)	 1 box = 5 sheets
Field Tile 	Hand-Cut Field Tile in 3x12 & 6x12	 3x12 box = 50 pcs or 12.5 sqft 6x12 box = 40 pcs or 20 sqft



Hexagon in Tundra Blend